

ENC Handheld screwing machine


ASA,KILEWS electric screwdriver + Scientific Design + Successful screw feeding
can reach 99.9% + Large capacity + Smart brain = Perfect performance in your work



Features:

- 1) Adopt the high quality ASA and KILEWS electric screwdriver.
- 2) The screw receiver nose can be designed base your screw,It can ensure the smooth and stable operation.Of course,It can supply you a perfect experience of screw assembly.
- 3) The outline of screw receiver nose is designed base on the condition around the screw,So it can meet your goods well.
- 4) The minimum distance between the screw head and the nearest obstacle can be 1.5mm.
- 5) The screw will be fed into the screw receiver nose rapidly and stably,Which can improve the efficiency of screw assembly much. It can reach 3 times productivity than manual.
- 6) Huge screw feeder,It can hold 500~4000 pieces screw.So you should never need to worry about the screw feeding.
- 7) The machine owns a intelligent brain,It can offer many special function as the following:Quantity statistics(OK amount and NG amount),thread slip detection,floating detection,screw omission detection and son on.

Suitable screw:



Condition:

$L \geq D+2\text{mm}; P \geq 1\text{mm}; L1 \leq 30\text{mm}$

NOTE:

If your screw can not meet this condition,Please refer p39 and P40.

Alternative pattern:

Two screwdrivers type



One screwdriver type



Specification:

Item/Model	ENC-1010	ENC-1016	ENC-1020	ENC-1025	ENC-1030	ENC-1036
Applicable screw (mm)	1.0~2.6		2.6~4.3		4.3~6	
Capacity (L)	≥0.5(≈0.4kg)		≥1.5(≈1.0kg)		≥1.5(≈1.5kg)	
Screw feeding pattern	Rocker arm /Screw feeder				Rocker arm / Vibrating bowl	
Air pressure (kg/cm²)	5.5(±0.5)					
Speed of Screw (Pcs)	44~55		30~50		30~50	
Power supply	110~240ACV,50/60Hz					
Feeding tube length (mm)	2000 (Can customized according to your require)					
Work temperature (°C)	-10~40					
Work humidity	20%~90%					
screwdriver configuration	One set		One set/Two set		One set/Two set	
Dimension (mm)	260x125x245		300x165x285		380x245x385	
Net weight (kg)	≈10		≈25		≈30	
Reference images	