

ENC Vibration bowl

Customized base on your screw and requirement = Perfect performance in your work



Reference images:



Clockwise exit

Anticlockwise exit

Three exits

Four exits

Features:

- 1) Customized according to your actual requirement and screw size.
- 2) Huge capacity,It can take 2000~30000 pcs of screws,Reduce the times of pouring screws much.
- 3) The reasonable design and firm structure makes feeding fast and stable.
- 4) Matched with the CHU power controller,Make it possible to control the feeding speed,set the starting mode etc.
- 5) Soft PE coating can protect appearance of your screws or samples well to keep good quality.
- 6) It also can feed screws with washer or spring washer well.
- 7) Standard type is matched with one outlet,If required,We can match 2~8 outlets for you.

Complimentary accessories:

Optional accessories:

Power controller	Power cord (Output)	Power cord (Input)	Ring & pad	Correlation photoelectric	Proximity switch
SDVC20-S	3 Pins	3 Pins	3 sets	Enlarged view	Enlarged view

Specifications:

Item/Model	VB-200	VB-300	VB-400	VB-500	VB-600	VB-D series
Capacity of screw (Pcs)	3000~8000	3000~7000	3000~7000	2500~6000	1000~3000	≥10000
Feeding speed (Pcs/Min.)	55~60	45~60	35~50	30~45	30~40	20~30
Power supply	100~260ACV,50/60Hz					
Dimension (Bowl dia. x H,mm)	200x300	300x320	400x360	500x420	600x500	Customization
Head diameter Max. (mm)	5	7	9	13	20	40
Total length Max. (mm)	8	10	20	30	50	100
Quantity of exit	1~12 (Design base on your actual requirement)					
Weight (Kg)	18	22	24	26	35	Customization
Complimentary accessories	Power controller,Power cord (Output),Power cord (Input),Fixing foot ring & Foot pad x 3					
Optional accessories	Correlation photoelectric,Proximity switch,Automatic screw supplying machine					

Technical matters to be confirmed before ordering:

- ① Your required capacity;
- ② Available space prepared for our vibration bowl (Length x Width x Height);
- ③ Direction of exit (Clockwise or Anticlockwise exit,Please check the "Reference images" above);
- ④ Requirement of screw appearance protection;
- ⑤ Exit quantity,Interval between two exits,Exit height;
- ⑥ Sample size;
- ⑦ Requirement of sound insulation;